



1" Aluminum Blind Specification Sheet

Headrail-Steel	Size: 1" x 0.97" x 0.035" Dimensions: Actual Width Cord Lock Location: 4" O.C. From End Tilter Location: 4" O.C. From End Tilt Rod Support Location: 6" O.C. From End
Bottomrail-Steel	Size: 0.77" x 0.39" x 0.024" Color: Coordinated Dimensions: Stated Width Less 1/2" Lift Cord Route Hole: 6" O.C. From End Warning Label On Right Side Of Bottomrail Country Of Origin Tag At Center Of Bottomrail
Slat	Curved Slat: Aluminum Slat Width: 25mm (1") Lift Cord Route Holes: 6" O.C. From End Thickness: 0.17 - 0.18mm (0.0067" - 0.007") After Painting Slat Count: 36" Drop = 43; 48" Drop = 58; 60" Drop = 72 72" Drop = 86; 84" Drop = 100 Braided Ladder: 21.3mm
Wand	Clear Acrylic Plastic Solid
Other	Color Coordinated slat clip. Clear Plastic Cord Lock Clear Plastic Double Rivet Tilter W/Metal Worm Gear Color Coordinated Tassels (2 Tassels For 2 Cords; 3 Tassels For 3 Cords) Color Coordinated Bottomrail End Plugs
Hardware	Steel H/R Brackets Color Coordinated "Bali" Style Zinc Plated Steel Center Support Bracket Hex Head Screws; 1-1/4" In Length
Packaging	Instruction Sheet Packed W/Blind Bubble Pack On Both Ends Blind In Polybag Wand Packed On Top Of Headrail Tassels Inside Of Headrail

Blind Width	Ladders	Cords	Slat Clips	Center Supports	Screws	Buttons	Hold Downs
0" - 31"	2	2	2	0	12	2	2
31.5" - 35"	2	2	2	0	12	2	2
36" - 58"	3	2	3	1	15	3	2
59" - 81"	4	4	4	1	15	4	2
82" - 104"	5	4	5	2	15	5	2
105" - 120"	6	4	6	3	15	6	2
Blind Width:	23"	27"	29" - 31"	Over 32" Wide			
Wand Length:	19.5"	24"	26"	30"			
Blind Drop:	35"	48"	59"	64"	71"	95"	
Control Cord Length:	23"	30"	35"	40"	55"	72"	